

# GRANIT™ ULTRA 2105i

## Ultra-Rugged Cordless Area-Imaging Scanner

Granit Ultra scanners expand capabilities and define the next generation of ultra-rugged scanning.

### ULTRA SCAN PERFORMANCE

For a scanner to optimize productivity, it should read and transmit common barcodes nearly as fast as the user can pull the trigger, and Granit Ultra is engineered to do just that. Granit Ultra integrates high speed processing, AI(Artificial Intelligence) algorithms, and decoding enhancements to result in an average 45% scanning speed increase vs. Granit XP<sup>1</sup>, enabling improved productivity.

### ULTRA DURABILITY

In modern warehouse, distribution center, and manufacturing environments, any scanner must be durable enough to survive harsh operating conditions. Under exactly that kind of rough treatment, Granit is ready to deliver.

### ULTRA EASE OF USE

Ready to operate right out of the box for many applications, Granit offers easy custom configuration in the time it takes to scan a barcode. For further workflow improvement, Granit can also read multiple codes in the field of view, organizing and outputting the data in a predefined order using Honeywell's Data Format Editor.

The all new charge and communication base is loaded with features to simplify common tasks. Easy drop-in charging makes scanner placement in the cradle fast and efficient for flat work surfaces; engaging the latching mechanisms helps ensure secure retention for vertical or vehicle mounting.



Honeywell Granit Ultra 2105i  
Ultra-Rugged Scanner

### SCAN MODELS

SR (Standard Range) models are ready to read barcodes from contact to arms length

XR (Expanded Range) models are ready to read UPC/EAN13 from contact to nearly 6' (1.8m), or up to 33' (10.85m) for 100 mil Code 39

## FEATURES AND BENEFITS



Built to survive harsh treatment including 3m (10ft) drops, 7500 1m (3.3ft) tumbles, operating temperatures from -20°C to 50°C (-4°F to 122°F), and IP65/68 sealing, Granit Ultra reduces service costs and increases device uptime.



Granit Ultra provides rapid scanning, even on damaged and low quality barcodes. High quality barcodes transmit faster than ever.



SR model reads from contact to arms length. XR model is ideally suited to near and mid-field scanning operations on 1D and 2D barcodes. For even longer reading distances, refer to XLR model in the Granit XP family.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

**Honeywell**

# Granit Ultra 2105i Technical Specifications

## MECHANICAL

**Scanner dimensions (L x W x H):** 194.8mm x 75.8mm x 139.5mm (7.7 in x 3.0 in x 5.5 in)

**Charge and Communication Base dimensions (L x W x H):** 250.1mm x 102mm x 80.7mm (9.8 in x 4.0 in x 3.2 in)

**Weight-Scanner:** 425g (15 oz)

**Weight—Charge and Communication Base:** 357g (12.6 oz)

**User Indicators:** Good decode LEDs, Battery Status LED, Bluetooth Connection Status LED, Beeper (adjustable tone and volume), Vibration (adjustable)

## ELECTRICAL

**Input Voltage:** 4.4VDC to 5.5VDC

**Operating Power(Charging):** 2.5W (500mA @ 5V USB 2.0)

**Operating Power(Charging):** 7.5W (1500mA @ 5V BC1.2 or external power supply)

**Standby Power:** 0.6W (120mA @ 5VDC)

**Host System Interfaces:** USB, Keyboard Wedge, RS-232 TTL (cables available to convert for +/-12V True use)

**Charging time:**

- USB 2.0:** <12 hours
- USB BC1.2:** <4 hours
- Power supply (5V 3A):** <4 hours

## POWER OPTIONS

**Battery:** 3300 mAh Li-ion

**Number of scans:** Up to 100,000 scans per charge

**Expected duration of operation:** 14 hours operating at 2 scans per second

## RADIO

**Bluetooth® v4.2;**

2.4 to 2.5 GHz (ISM Band)

Adaptive Frequency Hopping

**Class 1:** 100m (330 ft) line of sight with Honeywell Charge and Communication Base

## ENVIRONMENTAL

**Operating Temperature(non-charging):** -20°C to 50°C (-4°F to 122°F)

**Storage Temperature:** -40°C to 70°C (-40°F to 158°F)

**Charging Temperature:** 5°C to 35°C (41°F to 95°F)

**Humidity:** Up to 95% relative humidity, non-condensing

**Drop:**

- 3m (10 ft):** MIL-STD-810G, 25°C (77°F), 55% relative humidity
- 2.5m (8.2 ft):** 20 drops from -20°C to 50°C (4°F to 122°F), 55% relative humidity
- 2m (6.5 ft):** 50 drops from -30°C to 50°C (-22°F to 122°F), uncontrolled relative humidity

**Tumble:** 7,500 1m (3.3ft) tumbles

**Vibration:** Withstands 5G peak from 5 to 300Hz

**Trigger activations:** Tested to 3 million cycles

**Environmental Sealing:**

- Scanner:** IP65 and IP68
- Charge and Communication Base:** IP65

**Light Levels:** 0 to 100,000 lux (9,290 foot-candles)

**ESD:** +/-20KV air discharge, +/-8kV contact discharge, +/-8kV indirect coupling plane

## SCAN PERFORMANCE

**Scan Pattern -SR:** Area imager (1280x1080 pixel array)

**Scan Pattern -XR:** Near and Far: Area imager (1280x1080 pixel array)

**Illumination-SR:** Warm White 2700K LED

**Illumination-XR:** Yellow-Green LED

**Aimer -SR:** Green LED, 525nm peak wavelength

**Aimer-XR:** Green class 2 laser, 520nm peak wavelength

**Motion Tolerance:** Up to 4000 mm/s

**Scan Angle (Field of View):**

- SR:** Horizontal: 42°, Vertical 36°
- XR-Near:** Horizontal: 42°, Vertical 36°
- XR-Far:** Horizontal: 16°, Vertical 14°

**Print Contrast:** As low as 15%

**Roll, Pitch, Skew:** +/-360°, +/-65°, +/-65°

**Minimum Barcode Resolution:** 2.5 mil 1D, 5 mil 2D

**Image Capture:** Up to 109PPI on an A4 document

**Decode Capabilities<sup>2</sup>:**

- 1D:** Code 39, code 128, code 93, code 11, code 32 Pharmaceutical, codabar, EAN, UPC, China Post, GS1 databar
- 2D:** Aztec, Data Matrix, QR/Micro QR code, Maxicode, Chinese sensible (Han Xin) code, postal code, PDF417, DotCode,
- Digital Watermarking:** Digimarc
- OCR:** OCR A, OCR B, MICR E-13B and SEMI Font, in a 6 to 60 point OCR typeface

*Note: Decode capabilities dependent on configuration.*

## REGULATORY<sup>3</sup>:

**EMC:** EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Subpart B, ICES-003 Issue 7

**Safety, Health and Environmental Compliance:** EN62368-1, IEC 62368-1, IEC62471, IEC-63000(ROHS), UL 62368-1, CSA C22.2 NO. 62368-1, IEC60825 for XR model (laser)

**Radio:** FCC CFR Title 47 Part 15 Subpart C, RSS-Gen/RSS-247, EN 300 328.

**Accessories:** Stands, holders, holsters, power supplies, cables, heaters, charge and communication bases, Bluetooth access points, batteries.

**Warranty:** Three years factory warranty (Battery - one year)

**Services:** Honeywell Edge Service

**Utilities and Management:** EZConfig, SMU, Total Freedom, Scanner Edge, SDKs, Various Drivers

SYMBOLGY <sup>3</sup>	STANDARD RANGE(SR) - TYPICAL		EXPANDED RANGE(XR) - TYPICAL	
	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])
5 mil C39	10 [0.39]	269 [0.59]	10 [0.39]	269 [0.59]
10 mil C128	0 [0.0]	531 [20.91]	0 [0.0]	1,503 [59.17]
13 mil UPC	0 [0.0]	634 [24.96]	0 [0.0]	1,780 [70.08]
20 mil C128	0 [0.0]	1,033 [40.67]	0 [0.0]	2,812 [110.71]
100 mil C39	NA	NA	NA	10,848 [427.09]
6.7 mil PDF417	14 [0.55]	243 [9.57]	14 [0.55]	243 [9.57]
10 mil DataMatrix	5 [0.20]	261 [10.28]	5 [0.20]	261 [10.28]
20 mil QR Code	0 [0.0]	480 [18.9]	0 [0.0]	1,464 [57.64]
100 mil DataMatrix	NA	NA	NA	5,329 [209.80]

1. Honeywell standard benchmarking testing conducted on Granit Ultra SR and XR models vs. Granit XP on 6 collections of reference barcodes
2. For a complete listing of all supported barcode symbologies, please visit <http://honeywell.com/PSS-symbologies>.
3. Performance may be impacted by barcode quality and environmental conditions
4. For a complete listing of all compliance approvals and certifications, please visit [www.honeywell.com/PSScompliance](http://www.honeywell.com/PSScompliance).

To learn more about how Granit Ultra is ready to improve your operations, contact your Honeywell representative or partner today.

**For more information**  
automation.honeywell.com

**Honeywell Industrial Automation**  
855 S Mint St Charlotte, NC 28202  
800-582-4263  
www.honeywell.com

Honeywell standard benchmarking testing conducted on Granit Ultra SR and XR models vs. Granit XP on 6 collections of reference barcodes

Granit™ is trademark or registered trademark of Honeywell International Inc. All other trademarks are the property of their respective owners.

Granit Ultra 2105i Datasheet | Rev A | 03/25  
© 2025 Honeywell International Inc.

